

Teknisk data

Zirkon 8

buren, fast

Typ	8/250	8/300	8/350	8/400
Arbetsbredd (cm)	250	300	350	400
Vikt (kg) ¹	701	785	946	1.015
kW /hk (från - till)	44/60-103/140	55/75-118/160	62/85-125/170	66/90-129/175
Upp till PTO (rpm)	1.000	1.000	1.000	1.000
Rotorhastighet (rpm) vid 1000 rpm	300/400	300/400	300/400	300/400

Zirkon 12

buren, fast

Typ	12/300	12/350	12/400	12/450
Arbetsbredd (cm)	300	350	400	450
Vikt (kg) ¹	922	1.035	1.149	1.261
kW /hk (från - till)	66/90-154/210	77/105-165/225	88/120-176/240	88/120-176/240
Upp till PTO (rpm)	1.000	1.000	1.000	1.000
Rotorhastighet (rpm) vid 1000 rpm	230/330/440	230/330/440	230/330/440	230/330/440

Zirkon 12

buren, hydraulisk ihopfällbar

Typ	12/400 K	12/450 K	12/500K	12/600 K
Arbetsbredd (cm)	400	450	500	600
Vikt (kg) ¹	1.762	1.896	2.066	2.452
kW /hk (från - till)	88/120-199/270	99/135-199/270	121/165-221/300	132/180-235/320
Upp till PTO (rpm)	1.000	1.000	1.000	1.000
Rotorhastighet (rpm) vid 1000 rpm	230/330/440	230/330/440	230/330/440	230/330/440

Zirkon 12

delburen, hydraulisk ihopfällbar

Typ	12/400 KA	12/450 KA	12/500 KA	12/600 KA
Arbetsbredd (cm)	400	450	500	600
Vikt (kg) ¹	3.531	3.734	3.923	4.447
kW /hk (från - till)	88/120-199/270	99/135-199/270	121/165-221/300	132/180-235/320
Upp till PTO (rpm)	1.000	1.000	1.000	1.000
Rotorhastighet (rpm) vid 1000 rpm	230/330/440	230/330/440	230/330/440	230/330/440

Quarz 7

buren, fast

front buren, fast

Typ	7/300	7/400	7F/300	7F/400
Arbetsbredd (cm)	300	400	300	400
Vikt (kg) ¹ från	612	834	662	884
kW /hk (från - till)	49/67-93/127	60/82-104/142	49/67-93/127	60/82-104/142

¹ vikt utan vält

Korund 8	buren, fast	buren, hydraulisk ihopfällbar			
Modell	300	450 K	600 K	750 K	900 K
Arbetsbreite (cm)	300	450	600	750	900
Gewicht (kg) ab	872	1.410	1.952	2.860	3.268
kW/PS	48/65-85/115	70/95-107/145	77/105-129/175	92/125-158/215	107/145-180/245
Anzahl u. Breite der Felder	2 x 150 cm	3 x 150 cm	4 x 150 cm	5 x 150 cm	6 x 150 cm

System-Kompaktor	buren, fast	buren, hydraulisk ihopfällbar			
Typ	300 S	400 S	400 K	500 K	600 K
Arbetsbredd (cm)	300	400	400	500	600
Vikt (kg) ²	1.430	1.650	1.850	2.103	2.703
kW /hk (från - till)	55/75-85/115	70/95-114/155	70/95-114/155	107/145-158/215	121/165-180/245
Antal + bredd på harvsektion	2 x 150 cm	2 x 200 cm	2 x 200 cm	2 x 150, 1 x 200 cm	4 x 150 cm

System-Kompaktor	delburen, hydraulisk ihopfällbar	
Typ	500 KA	600 KA
Arbetsbredd (cm)	500	600
Vikt (kg) ²	3.670	4.270
kW /hk (från - till)	100/136-158/215	114/155-180/245
Antal + bredd på harvsektion	2 x 150, 1 x 200 cm	4 x 150 cm

System-Kompaktor	bogserad, hydrauliskt ihopfällbar		
Typ	Gigant 10/800	Gigant 10/1000	Gigant 12/1200
Arbetsbredd (cm)	800	1000	1.200
Vikt (kg) ²	2.630	2.830	4.740
kW /hk (från - till)	158/215-232/315	202/275-346/470	246/335-404/550
Antal + bredd på harvsektion	4 x 200 cm	4 x 150, 2 x 200 cm	6 x 200

²vikt med Crosskill vält