

Teknisk data

Heliodor 8	buren, fast			buren, hydraulisk ihopfällbar			
Typ	8/250	8/300	8/350	8/400	8/400 K	8/500 K	9/600 K
Arbetsbredd (cm)	250	300	350	400	400	500	600
Vikt (kg) ¹	672	805	912	1.020	1.727	1.848	2.110
kW /hk (från-till)	46/63-74/100	55/75-88/120	65/88-103/140	74/100-118/160	74/100-118/160	92/125-147/200	110/150-176/240
Tallrikar (antal/ Ø mm)	20/465	24/465	28/465	32/465	32/465	40/465	48/465

Heliodor 8	semi-buren, hydraulisk ihopfällbar			bogserad, hydraulisk ihopfällbar		
Typ	8/400 KA	8/500 KA	8/600 KA	Gigant 10/800	Gigant 10/1000	Gigant 10/1200
Arbetsbredd (cm)	400	500	600	800	1.000	1.200
Vikt (kg) ¹	2.437	2.626	2.794	4.650	5.296	6.452
kW /hk (från-till)	74/100-118/160	92/125-147/200	110/150-176/240	174/235-118/320	184/250-294/400	221/300-353/480
Tallrikar (antal/ Ø mm)	32/465	40/465	48/465	64/465	80/465	96/465

Rubin 9	buren, fast			buren, hydraulisk ihopfällbar				
Typ	9/250 U	9/300 U	9/350 U	9/400 U	9/400 KU	9/450 KU	9/500 KU	9/600 KU
Arbetsbredd (cm)	250	300	350	400	400	450	500	600
Vikt (kg) ¹	1.480	1.640	1.800	1.960	2.890	3.111	3.331	3.785
kW /hk (från-till)	64/87-92/125	77/105-110/150	90/122-129/175	103/140-147/200	103/140-147/200	115/157-165/225	129/175-184/250	154/210-221/300
Tallrikar (antal/ Ø mm)	20/620	24/620	28/620	32/620	32/620	36/620	40/620	48/620

Rubin 9	delburen, hydraulisk ihopfällbar			bogserad, hydraulisk ihopfällbar			
Typ	9/400 KUA	9/450 KUA	9/500 KUA	9/600 KUA	Gigant 10 S/800	Gigant 12 S/1000	Gigant 12 S/1200
Arbetsbredd (cm)	400	450	500	600	800	1.000	1.200
Vikt (kg) ¹	3.652	3.961	4.241	4.921	9.966	10.936	12.382
kW /hk (från-till)	103/140-147/200	115/157-165/225	129/175-184/250	154/210-221/300	206/280-294/400	257/350-368/500	309/420-441/600
Tallrikar (antal/ Ø mm)	32/620	36/620	40/620	48/620	64/620	80/620	96/620

Rubin 12	buren, fast			semi-buren, hydraulisk ihopfällbar		
Typ	12/300 U	12/350 U	12/400 U	12/400 KUA	12/500 KUA	12/600 KUA
Arbetsbredd (cm)	300	350	400	400	500	600
Vikt (kg) ¹	2.046	2.141	2.616	4.402	5.284	5.732
kW /hk (från-till)	99/135-177/240	116/158-206/280	132/180-235/320	132/180-235/320	165/225-294/400	199/270-353/480
Tallrikar (antal/ Ø mm)	18/736	18/736	22/736	22/736	30/736	34/736

Kristall 9	buren, fast			buren, hydraulisk ihopfällbar		
Typ	9/300	9/350	9/400	9/400 K	9/500 K	9/600 K
Arbetsbredd (cm)	300	350	400	400	500	600
Vikt (kg) ¹	772	871	990	1.445	1.543	1.861
kW /hk (från-till)	66/90-99/135	77/105-116/158	88/120-132/180	88/120-132/180	110/150-165/225	132/180-199/270
Pinnar/ tallrikspar	7/3	7/3	9/4	9/4	11/5	13/6

Kristall 9	delburen, hydraulisk ihopfällbar		
Typ	9/400 KA	9/500 KA	9/600 KA
Arbetsbredd (cm)	400	500	600
Vikt (kg) ¹	3.030	3.128	3.446
kW /hk (från-till)	88/120-132/180	110/150-165/225	132/180-199/270
Pinnar/ tallrikspar	9/4	11/5	13/6

Karat 9	buren, fast			buren, hydraulisk ihopfällbar	
	9/300	9/350	9/400	9/400 K	9/500 K
Typ	9/300	9/350	9/400	9/400 K	9/500 K
Arbetsbredd (cm)	300	350	400	400	500
Vikt (kg) ¹	850	950	1.050	1.665	1.855
kW /hk (från-till)	77/105-110/150	90/122-129/175	103/140-147/200	103/140-147/200	129/175-184/250
Pinnar/ tallrikspar	11/3	12/3+1 St.	14/4	14/4	17/5

Karat 9	delburen, hydraulisk ihopfällbar				Lätt transportchassi, hydraulisk ihopfälling			
	9/400 KA	9/500 KA	9/600 KA	9/700 KA	9/400 KTA	9/500 KTA	9/400 KUTA	9/500 KUTA
Typ	9/400 KA	9/500 KA	9/600 KA	9/700 KA	9/400 KTA	9/500 KTA	9/400 KUTA	9/500 KUTA
Arbetsbredd (cm)	400	500	600	700	400	500	400	500
Vikt (kg) ¹	3.747	4.157	4.557	5.067	3.165	3.355	3.625	3.965
kW /hk (från-till)	103/140-176/240	129/175-221/300	154/210-265/360	180/245-309/420	103/140-147/200	129/175-184/250	103/140-147/200	129/175-184/250
Pinnar/ tallrikspar	14/4 + 1 St.	18/6	21/7	25/8	14/4	17/5	14/4	17/5

Smaragd 9	bogserad, hydraulisk ihopfälling		
	Gigant 10/800	Gigant 10/1000 ²	Gigant 12/1200 ²
Typ	Gigant 10/800	Gigant 10/1000 ²	Gigant 12/1200 ²
Arbetsbredd (cm)	800	1.000	1.200
Vikt (kg) ¹	5.419	6.975	9.355
kW /hk (från-till)	147/200-265/360	184/250-331/450	221/300-397/540
Pinnar/ tallrikspar	18/8 + 1 St.	22/10 + 1 St.	26/12 + 1 St.

Topas 140	buren, fast		
	140-5	140-7	140-9
Typ	140-5	140-7	140-9
Arbetsbredd (cm)	250	300	400
Vikt (kg)	381	415	540
kW /hk (från-till)	51/70-99/135	66/90-110/150	74/100-125/170
Antal pinnar	5	7	9

Dolomit 9	buren, fast	
	9/300	9/400
Typ	9/300	9/400
Max redskapsbredd (cm)	35	35
Vikt (kg)	430	550
kW /hk (från-till)	59/80-125/170	74/100-147/200
Pinndelning	75	75
Antal pinnar	4	6

Labrador 160	buren, fast	
	65	225
Max redskapsbredd (cm)	65	225
Vikt (kg)	485	225
kW /hk (från-till)	55/75-129/175	225
Pinndelning	100-225	225
Antal pinnar	2	225

¹Vikt utan vält

²Gigant 10/1000 och Gigant 12/1200 Smaragd endast möjlig med mekanisk Non-Stiop överbelastningskydd