Mamut



Dimensions

Type	A	В	C	D	Е
Mamut 21	3500	7500	4700	1000	2800
Mamut 24	3500	7500	4700	1000	2800
Mamut 28	3500	8500	4700	1000	2800
Mamut 30	3500	8500	4700	1000	2800
Mamut 36	3500	8700	4700	1000	2800

E Indicated width of the sprayer

Weight

Work. width (m)		Full
21 - 36	kg	kg
Mamut 4000	4000 - 4900	8400 - 9400
Mamut 5000	4100 - 5000	9500 - 10500
Mamut 6000	4200 - 5100	10600 - 11600
Mamut 6500	4250 - 5150	11150 - 12150

Booms and tank

Work. width (m)	Content (1)
21 - 36	4000 - 6500

Wheels

• wheels 520/85 R42 168 A8

Description

Chassis / Axles

- upper hinging, towing eye Ø 40 mm
- fixed extendable axle ADR 10 t
- wheels 520/85 R42 168 A8

Pumps / Filling

- · homokinetic joing drive
- pump AR 280 (up to 30 m)pump 2x AR185 (above 30 m)
- outside filling and suction 2"

Water / Tank

- fibre glass tank with breakwaters 4000 I
- pneumatic spraying regulation
- internal flushing of the tank
- · pressured mixing and overflow mixing
- eco Comfort Fill 60 I induction hopper
- clean water tank 500 I
- watermark

Computer / Electronics

počítač SPRAYDOS

Boom / Distribution

- 6 8 sections
- · boom with active tilting
- potentiometer
- full suspension of boom
- stainless distribution in boom \varnothing 20 mm with triple nozzle holders 50 cm apart

Others

- hydraulics controlled from the tractor by two hydraulic circuits
- lightning for road use

MAMUT with 4000 - 6500 I tank is one of the most common sprayers from the whole range of Agrio. It allows big daily output in a larger farm or agricultural company and outside of the main spraying season it is not necessary to bring water to the field that often